

Battery module for UPS2 emergency power supply



- Set consisting of power supply unit, battery module, lead battery 4Ah
- Uninterruptible power supplies are designed for automation, access control and security systems where a continuous supply must be guaranteed
- The battery used is a 12V – 4Ah (hermetic lead battery)
- A replaceable microfuse is also integrated in the battery module to protect the battery
- The maximum applicable capacity is 14Ah
- Furthermore, we recommend for the disposal of used rechargeable batteries, to observe the national ordinance

Technical specifications:	
Input voltage	230 VAC
Output voltage	12 VDC
Overload capacity	None
Current Ampere	500mA
Power	4Ah
Connection type	Screw connection
Function	DC – UPS
Signal contact	No
Dimmable	No
Mounting	Top-hat rail
Protection class	IP20
Function display	LED
Satelco Article no.	10655
Included items	Power supply unit, battery module, lead battery 4Ah

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch

* Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as “front accessible” can be accessed by the customer.