

## Datasheet Ingenium BES KNX SmartTouch ST2-K Plus

### Ingenium BES KNX SmartTouch ST2-K Plus



- **ST2-K is the new version of the SmartTouch-K**
- 4.3" vertical colour touch screen to control and monitor all installation devices through icons on customisable images
- Integrated WEB server or the possibility to create a WiFi network to enable on-site and/or remote control from any iOS or Android device
- Supports up to 32 control elements, divided into 4 pages (8 controls per page) whose navigation is done by a simple sideways movement
- Special interface for climate control with an internal thermostat
- Also includes gestural «shortcuts» that allow you to perform standard actions with a simple movement while the screen remains in standby mode
- Multilingual support and security aspects such as locking by a numerical code or restricting access to the settings menu

The SmartTouch ST2-K is available with the back panel in WHITE or BLACK.

Technical data:	
Supply	18 to 30V DC from auxiliary power supply
Consumption	130mA from auxiliary power supply
<b>It is not possible to use the auxiliary output of the KNX power supply. It is possible with Ingenium power supply.</b>	
Consumption	1mA from KNX Bus
Temperature range	-10° C to + 60° C
Mounting	Mounted on universal box, screwed to the wall
Dimensions	88 x 129 x 2mm (12mm depth)
Certification	According to the Electromagnetic Compatibility Directive and the Low Voltage Directive. EN 50090-2-2 / UNE-EN 61000-6-3:2007 / UNE-EN 61000-6-1:2007 / UNE-EN 61010-1

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. [www.satelco.ch](http://www.satelco.ch)

\*Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as „front accessible“ can be accessed by the customer.

H:\1 Produkte\3 Automation\2 KNX Automation\1-BES KNX SmartTouch-ST2-K Plus