



**Network Dome Camera Day/Night**

- Sensor: 1/2.8" Sony Starvis CMOS
- Lens: F1.4/2.8-12mm (83 – 35°)
- Lux 0.1, 3 MP, IR illumination approx. 25m
- PoE, 12 VDC
- Browser independent (IE, Safari, Firefox, Chrome)
- Increasing the frame rate during motion
- OpenVPN support
- Indoor application

<b>Technical data:</b>	
<b>Housing and assembly</b>	
Dimensions	94 x 130 mm
Camera shape	Dome
Housing	Interior plastic
Colour	White
Mounting	Wall or ceiling mounting
Operating temperature	-10°C to +50°C
<b>Video properties</b>	
Resolution standard	3 Megapixel
Max. Image resolution	2048 x 1536
Max. Frame rate	30 fps
Video compression	H.264 / M-JPEG
Image sensor chip size (inch)	1/2.8"
Light sensitivity	50 IRE, at F1,4
Illumination / Range	Infrared, approx. 25m
Lens Type	Varifocal (motorised)
Zoom Factor	4x / digital
Focal length	2.8 – 12mm
Horizontal angle of view	83 – 35°
Control interfaces	Ethernet – 10Base-T / 100Base-TX
<b>Audio</b>	2 way audio
<b>Power over Ethernet</b>	IEEE 802.3af
<b>Power supply</b>	12 VDC / PoE
<b>Category</b>	Dome cameras IP
<b>Brand</b>	ENEO – IED-63M2812P0A
<b>Satelco Article number</b>	<b>11400</b>

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. [www.satelco.ch](http://www.satelco.ch)  
 \* Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.