

Network Bullet Camera Day/Night



- Sensor: 1/2.8"
- Lens: F1.6/2.7 – 13.5mm (97 – 29°)
- Lux 0.05, 5 MP, IR Illumination approx. 40m
- PoE, outside, IP67
- Integrated connexion box incl. connection board
- Browser independent (IE, Safari, Firefox, Chrome)
- Supports ONVIV Profiles S and T

Technical data:	
Housing and assembly	
Dimensions	130.5x82.1x265.1 mm
Camera shape	Bullet
Housing	Exterior, aluminium
Colour	Pantone Cool Gray 1 C
Mounting	Wall or ceiling mounting
Protection type	IP67
Operating temperature	-50°C to +50°C
Video properties	
Resolution standard	5 Megapixel
Max. Image resolution	2560 x 1944
Max. Frame rate	30 fps
Video compression	H.264 / H.264+ / H.265 / H.265+ / M-JPEG
Image sensor chip size (inch)	1/2.8"
Light sensitivity	0.05 Lux / at F1.6 / 40 IRE
Illumination / Range	Infrared, approx. 40m
Lens Type	Varifocal (motorised)
Zoom Factor	4x / digital
Focal length	2.7 – 13.5mm
Horizontal angle of view	97 – 29°
Control interfaces	Ethernet – 10Base-T / 100Base-TX
Audio	2 way audio
Power over Ethernet	IEEE 802.3af
Power supply	PoE
Category	Bullet cameras IP
Brand	ENEO – ICB-65M2713M5A
Satelco Article number	11402

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch
 * Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.