



Gigaset Cordless Phone SL930S DECT Sallegra® Edition



IP-SIP/VoIP Cordless DECT Phone

- User-friendly 3.2" colour touch screen
- DECT Phone with Android and WLAN
- Power over Ethernet integrated
- Up to 6 VoIP accounts
- Up to 4 external calls simultaneously
- Up to 2'000 contacts as vCard
- Access to local network phone books and public online phonebooks
- Caller identification (CLIP)
- Notification and reading function for e-mails
- Answering machine with up to 55 min recording time
- Sallegra[®] App to control your smart home and audio/video communication with SIP door intercom system

Technical data:	
Operating system	
	Android 4.0.4 (Ice Cream Sandwich)
IP Protocols	
	 SIP (RFC3261, RFC2396, RFC2976) HTTP authentication/Digest Access Authentication (RFC2617) Localisation of SIP servers (RFC3263) Transfer the call (RFC3515, RFC3891, RFC3892) MWI (RFC3265, RFC3842) SDP (RFC4566, RFC3264, RFC3555) RTP (RFC3550, RFC3551, RFC3555, RFC2833) XML based Gigaset online phone book protocol, HTTP, SNTP, STUN, POP3, DHCP (Option 60, 114, 120), DNS, TCP, UDP, IPv4, QoS, VLAN Codecs G.711, G.722, G.726, G.729ab VAD/CNG QoS
Touch-Display	
	3.2" Full-Touch TFT display (45 x 68 mm / 8.1 cm diagonally), resolution 320 x 480 pixels, simple operation with tipping/wiping function 5 freely configurable start screens with favourite tray and adjustable widgets
Power Supplay	
Base station	AC adaptor or PoE (IEEE 802.3af, Class 3)
Charging tray	AC adaptor
Mobile handset	Internal lithium-ion battery3.7 V / 1300 mAh
Memory	
	4 GB – Expansion via microSD card up to 32 GB (microSD card not included)

Satelco AG | Seestrasse 241 | 8804 AU-Wädenswil (CH)

Tel. +41 (0)44 787 06 07 | Fax: +41 (0)44 787 06 08 | E-Mail: satelco@satelco.ch | www.satelco.ch



Interfaces	
Mobile handset	Micro USB, Micro-SD slot, 3.5 mm jack for stereo headset
Base station	1 Ethernet port RJ-45 , LAN speed 10/100 Mb/s
DECT-Interface	
Frequency range	1.88 to 1.90 GHz (EMEA), DECT modulated
	DECT EN 300 175-x
DECT radio transmission	Up to max. 50 m outdoors and 300 m in buildings
	Latest DECT security standard
Standards	
	DECT, GAP, WLAN 2.4 GHz IEEE 802.11b/g/n
Mobile handset	
Functions	Gigaset QuickSync / vibration alarm / Sallegra® building automation
Standby time	Up to 140 h
Talk time	Up to 20 h
Battery	Li-Ion 3,7 V / 1300 mAh
Charging time	approx. 4 h
High quality keys	Call (talk key) green illuminated, on-hook/disconnect key (On/Off) red illuminated, 3 function keys
Optical call signalling	Illuminated display, flashing call key
Number of mobile handsets	Can be expanded by 5 mobile handsets
PC connection	Per Micro-USB with software Gigaset QuickSync (data cable not included Download pictures for Picture CLIP, Screensaver, slide show and sounds for ringtones (JPEG, BMP, MP3, etc.)
Audio-Functions	
	Brilliant sound quality with HDSP
	Comfortable hands-free operation (full duplex quality), adjustable handset volume
	21 preinstalled ringtones, uploading own ringtones possible
	Vibration alarm
Phone book and call manageme	ent
Address book and calling options	 Access to phone / address book of your handset / public online phone book / personal online telephone directory Reverse search and automatic on-line search Android address book for up to 2,000 vCards (first and last name, 3 phone numbers, e-mail, anniversary, and reminder time) Automatic synchronisation of Google contacts via WLAN Phone number transmission for incoming and outgoing calls List of missed calls and redial list Redial the last 20 numbers Search function Automatically dial a preselection or network preselection Dialling: tone dialling (DTMF), flash adjustable Support for network performance features
Call display / call signalling	 With call number or name (CLIP/CNIP) With the picture of the caller (Picture CLIP) Pictures for Picture CLIP and individual melodies (JPEG, BMP, MP3) Vibration alarm Individual ringtones for external/internal calls
Incoming calls	 Automatic on-line search For outgoing, received, and missed calls (20 entries each) with date and time Call waiting, forward and transfer call, reject call Hold and resume the call Waiting music Lock anonymous callers DTMF (SIP-INFO/RFC2833)

Satelco

Traditional functions of a telephone system	 Conferences Transfer call: with demand, with initial demand Hold the call Forward call: CFU, CFNR, CFB No MWI display when call is terminated elsewhere Call list Reject the call Resume the call Call-back Suppress phone number transmission CLIR Call waiting Auto Provisioning
Integrated answering machine	
Answering machine recording time	55 min
Remote enquiry	Yes
Voicemail	
	SIP MWI signalling / MWI key
E-Mail	
	Set up and manage up to six e-mail accounts, send and receive e-mail
Supported protocols	POP3/IMAP4/Microsoft Exchange ActiveSync
Entertainment	
	Load pictures, videos and music files – in the phone up to3 GB, on an optional microSD card up to 32 GB
Pictures	As a background, for Picture CLIP / Screensaver (picture gallery)
Pictures – playback	Decoder Format - supported file formats: JPEG/GIF/PNG/BMP/WebP
Video	Compile pictures and video clips in a movie / add effects and add music
Video – playback	Decoder Format – supported file formats: 3GPP/MPEG-4/MPEG-TS/3GPP/WebM/Matrska
Music	Load and listen to music files
Audio – playback	Decoder Format – supported file formats: MP3/3GPP/MP4/Midi (.MID, .OTA, IMY)/ FLAC/ Ogg vorbis/8- and 16-Bit (.WAV)
Audio – recording	Encoder Format – supported file formats: 3GPP/MP4/
Other functions Organiser	Calendar, scheduler / alarm clock with snooze function / separate ringtone media adjustable
ECO DECT	
	Automatic reduction of the radiation the closer the handset is at the base station
Eco mode	Low radiation when talking on the phone: 80% reduction of the radio performance when the Eco mode is activated
Eco mode+	Radiation-free in standby mode with activated Eco mode+
Dimensions/Technical data	
Colour	Mobile handset: Metal – Piano black / Base station: Polar white
Dimensions / handset weight	134 x 58 x 16 mm (H x W x D) / 174 g incl. battery
Dimensions / base station weight	115 x 117 x 45 mm (H x W x D) / 125 g
Approvals	CE
Scope of delivery	
	Mobile handset with charging base, DECT IP base station, Ethernet cable RJ-45, 2 power supply units
	Pre-programmed for Sallegra® building automation

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch

^{*} Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.