



Smoke, Humidity, Temperature Sensor VT460

- **Sensor connection with RJ12 patch cable**
- **Early detection of smoke, humidity and temperature**
- **Display in the web interface**
- **The warning detector is always mounted with the sensor head downwards**
- **It must be positioned in such a way that it is sufficiently ventilated and the ventilation slots are not covered**
- **Dry contact Mounting**

Dimension	Ø100×45 mm
Weight	290 gr
Inputs	2 x RJ12
Operating temperature	Min. -10° C, Max.80° C
Operating humidity	Min. 5% - Max. 95% (non-condensing)
Power consumption	100 mW
Status display	Red LED
max. Distance to the unit	225 m
HS Code	8531 10 950
Special features	Daisy-Chain
Mounting	On the ceiling
Satelco Article number	11382

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. www.satelco.ch
 *Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.