



**Monitoring System VT335s**

Simple, reliable monitoring unit with digital inputs for cost-effective remote monitoring of computer rooms with all kinds of sensors. Order option:

- a) EU AC power supply 12V / 1A; or
- b) 48V DC version: mounted in DC power supply 48/12V

**Accessories:**  
**Rackmount Kit Satelco Monitoring System VT335S / Art. No: 11163**

Technical data:	
Dimensions	206 x 33.1 x 79.4mm
Weight	1.2Kg
Power Input	Order option: A) EU AC Power Adapter 12V / 1A; or B) 48V DC version: Mounted in DC power supply 48/12V.
Power consumption	6 Watt
Operating temperature	temperautre : Min. -10° C - Max.+80° C
Other	Chassis grounding (M4 thread) Recovery switch Restore switch
Mounting options	VT122 / 19-inch bracket (to be ordered separately) VT123 / Wall brackets (to be ordered separately) VT124 / DIN rail mounting (to be ordered separately)
Max. Distance from device	225 M
HS-Code	8471 50 000
The package includes	Patch cable RJ-45 1m Self-adhesive rubber foot 4 pcs. Brief description and connection instructions Connector plug 3-pole 3.81mm 1pc. Connector plug 6-pin 3.5 mm 1pc. USB min to USB cable For VT335 S 12V: 12 V EU AC adapter Warranty card
Brackets (accessories)	VT10 / 1-wire module VT122 / 19-inch bracket VT123 / wall bracket VT124 / DIN rail bracket VT700 / GSM modem VT760 / LTE, GPS modem VT
Inputs Connection terminals	Analog sensor ports: X4 ports CAN bus sensor connection Dry contacts / Digital inputs: 4 contacts (3.5mm pitch, IN type)
Processor	ARM926-300 MHz / 64 MB / Linux-2.6.38
Protocols extension	1-Wire /CAN
Network interface	1-wire (with extension) CAN bus Ethernet 10/100 Mbit/S
Integrated sensors	Temperature sensor (accuracy 1%)
Status displays	Error LED LED indicator for CAN bus connection LED indicator for power/network connection Relay status LEDs
<b>Satelco Article number</b>	<b>11156</b>

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. [www.satelco.ch](http://www.satelco.ch)  
\*Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.