



Satelco Li-ION Battery CGA103

- Li-Ion, 1850 mAh Battery
- For installation in the monitoring units VT825 and VT825DC
- Used as a backup power source
- Connected to the DC 12V backup power connector
- Requires VT101 – battery holder and VT18 – expansion board

Dimensions	52 x 101 x 15 Mm (L x W x H)
Weight	133 g
Operating temperature	Min. 0° C - Max. +45° C
Mounting	Desk, wall-mounted
HS-Code	8507 60 00
Special features	Li-Ion, 1850 MAh, voltage - 11,1 V
Satelco Article number	11188 - CGA103
Satelco Article number	11187 - VT101

Battery holder VT101



Used like a buffer battery holder, can be attached to the VT825 housing.

Dimensions: 122 x 62 x 44mm

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. www.satelco.ch
 *Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.