

## VTX40 Dry contact board (IN/OUT)



- Extension unit for floating contacts
- 2-wire interface has x32 dry contact inputs and x8 dry contact outputs
- Web interface
- Enables addressed correlation of dry contact reactions and allows appropriate measures to be determined by the system logic

<b>Operating temperature</b>	Min. -10° C - Max.+80° C
<b>Mounting options</b>	Built in unit, Replaces VTX16
<b>Inputs Terminals</b>	X32 Floating contact inputs
<b>Outputs Terminals</b>	X8 Isolated potential-free contact outputs
<b>Package contains</b>	BH-10 Bus Cable, X8 Terminals (6P 3.5mm), X2 Terminals (8P 3.5mm), X5 Screws
<b>HS Code</b>	8531 10 300
<b>Device management</b>	Web interface has «dry contacts» panel
<b>Dimensions</b>	241 x 35 x 11 mm (L x W x H)
<b>Satelco Article number</b>	<b>11164</b>

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. [www.satelco.ch](http://www.satelco.ch)

\*Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.