

**Satelco Humidity sensor VT510**



- **Measurement and monitoring of humidity in technical and server room infrastructures**
- **Measurement and monitoring of humidity in production environments**
- **Long-term measurement of relative humidity in warehouses, depots and archives**
- **Supervision and monitoring of air conditioning and ventilation systems**
- **Automation technology**
- **House and building technology**
- **Avoidance of mould formation (black mould etc.)**

**Suitable for: all IP thermo-/hygrometers, monitoring systems and PDUs**

<b>Dimension</b>	81 x 18 x 18 mm (L x W x H)
<b>Weight</b>	16 g
<b>Power consumption</b>	60 MW
<b>Operating temperature</b>	-40° C to +100° C
<b>Measuring range</b>	0% to 95% relative humidity (RH)
<b>Mounting</b>	Table / ceiling / wall mounting / mounting in IT racks
<b>Extendable</b>	Optionally removable up to 100 metres away
<b>HS-Code</b>	9025 11 800
<b>Accuracy</b>	+ / - 3% RH
<b>Inputs</b>	RJ11 6P4C Terminals
<b>Satelco Article number</b>	<b>11319</b>

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. [www.satelco.ch](http://www.satelco.ch)

\*Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.