



- Simple installation
- 1W Speaker
- Tamper switch
- Full-Duplex

Universal IP Intercom solution

2N IP Uni, is a SIP Intercom which provides a cost effective solution for access control and communication. It offers full-duplex audio with echo cancellation, integrated relay for door entry systems and 1 or 2 fully backlit buttons. 2N IP Uni is ideal for schools, parking lots, shopping malls, hospitals or public buildings. It can be used as an information/emergency help point or as a door entry system.

Due to its innovative design and available accessories, 2N IP Uni will save you time needed for installation and offers you variety of mounting options such as on the wall, plasterboard or flush mount.

Highlights:

- Cost effective door IP Intercom solution
- Relay controlled by DTMF
- Stainless steel front panel
- Compatible with 2N Access Commander

Features:

- Simple installation
- 1W Speaker
- Fully back-lit buttons
- Integrated Tamper switch
- Times profiles integrated
- DTMF Switch control
- 2N Access Commander Application

Target Groups:

- Schools
- Hospitals
- Residential
- Public areas



All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch

Technical Data:	
Signalling protocol	SIP 2.0 (RFC – 3261)
Buttons	
Button version	Fully back-lit
Number of buttons	1 or 2
Pictogramms	optional (visual status display for call setup, speaking, door open)
Audio	
	Full-Duplex, echo cancellation
Mircrophone	1 integrated microphones
Speaker	1W
Audio stream	
Codecs	G.711
Interface	
Power	12V+/- 15%/AA DC or PoE
PoE	PoE 802.3af (Class 0 – 12.95W)
LAN	10 / 100BASE-TX with Auto-MDIX
Passive switch	NC / NO contacts, max 30V/ 1A AC/DC
Active output of switch	12V / 700mA DC
Mechanical	
Operating temperature	-40°C – 55°C
Storage temperature	-40°C – 70°C
Storage relative humidity	10% - 95% (non-condensing)
Dimensions	193 x 115 x 57 mm (max)
Protection level	IP54
Mounting	flush-mounting/surface-mounting/stand pillar (<i>surface mount box must be ordered separately</i>)

Added functionality with license upgrade is not possible!

* warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / **NOTE:** Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.