

Mounting accessories:



2N Force/Safety in-wall housing
In-wall housing for mounting in bricks or clinker



2N Force/Safety in-wall housing
In-wall housing for mounting in plasterboard



2N Safety frame
Frame for mounting in plasterboard, orange



Gooseneck stand for 2N Force and 2N Safety
Height 120 cm



Security Screws 2N IP Force

IP relays:



2N IP Force/Safety 2nd relay
Additional switching contact for assembly in 2N IP Force/Safety



Sallegra IP relay
4-channel module mounted on DIN rail
12 V DC supply



2n Security Relay
External relay connected with a special code

Power supply unit:



DIN housing 12 V DC supply
12 V DC / 1A or 12 V DC / 2A power supply unit



PoE Injector
Power over Ethernet injector (feed-in) for 2N IP power supply via Ethernet

All specifications are subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. www.satelco.ch

* Warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.