



IP Video Intercom

The robust front panel of the intercom is made of aluminium, anodised and equipped with a ball head colour camera, loudspeaker, microphone, 2 push-buttons, 2 name plates.

Technische Besonderheiten:

- VoIP communication via SIP 2.0
- SIP rear electronics with Ethernet connection
- Use of the LAN / WLAN network for administration, communication and control via web browser
- Supply via a power supply unit or PoE
- Location determination via SMS geofencing

Special production on request,
individually configured for you.



Technical data :	
IP Parameter	
Signalling	SIP 2.0 (UDP)
Audio Codec	G.711
Audio protocols	RTP (G.711)/ RTSP
IP protocols	IPv4, ARP, TCP, UDP, DHCP, HTTP/ HTTPS, SNMP, TFTP, SMTP, ONIV
Power supply	
External	12 V DC (9-36 V DC), max. 2 A
PoE (Power over Ethernet)	802.3af (Class 0 – Max. 12.95 W)
Consumption	2 W in standby mode
Ethernet Interfaces	
LAN	2x LAN (1+2), 10/100BASE-TX mit Auto-MDIX, RJ45 PoE 802.3af (only LAN 1)
Recommended cable	Cat-5e und better
Audio / Video	
	Loudspeaker, Microphone, Colour camera (adjustable horizontal viewing angle 68°)
Mecanical properties	
Front panel	Aluminium anodized, transparent
Front panel dimensions	Depending on configuration
Operating temperature	-40 °C to +55 °C
Humidity	10 % bis 95 % (non-condensing)
Storage temperature	-40 °C to +70 °C
IP rating	IP 20
Assembly	Flush mounted

All specifications are subject to change without notice or obligation to provide such changes to previous customers. The information and specifications published hereunder are current as of the date of publication of this document. We reserve the right to change specifications without prior notice. www.satelco.ch
Warranty Ex Works, normally 24 months, to be determined at time of order. Information is current at the time of publication. Specifications are subject to change without notice. / NOTE: Internal connections refer to connections inside the equipment, usually on a header. External connections refer to connections outside the enclosure. Once the unit is mounted, only the connections designated as "accessible from the front" are accessible to the customer.