

## Datasheet iTach TCP/IP to IR with PoE

### iTach TCP/IP to IR (infrared control) with power via Ethernet PoE



- **Integrated web server for easy configuration, HTTP, DHCP**
- **Power supply via Ethernet (PoE) activated**
- **Supports up to 8 simultaneous connections**
- **Instantly connects almost any electrical device to an Ethernet network**
- **IR learning built into each unit**
- **Ultra-compact design, stylish case fits almost anywhere**

<b>Technical data:</b>	
<b>Power supply</b>	
	230V AC to 12V DC 500mA
	PoE (Power over Ethernet) 802.3af
<b>Network Connection</b>	
iTach IP2IR / iTach IP2IR-P	RJ45 LAN; 100/10 Mbits Ethernet-Protocol
iTach WF2IR	Industry standard WLAN 802.11b with 2.5" antenna
<b>IR at sensor interfaces</b>	
	3 Independent selectable IR outputs or sensor inputs
	3.5 mm stereo jack
	3 IR emitters included
	1 IR blaster included (supported on 3rd IR port)
<b>LED indicators</b>	
	To display current at connections
<b>Enclosure</b>	
	Extruded aluminium housing, rubber end caps and plastic front panels
<b>Dimensions / Weight</b>	
	82 x 57 x 32 mm (W x H x D) / 92gr.

All specifications subject to change without notice or liability to provide changes to prior purchasers. Information and specifications published here are current as of the date of publication of this document. We reserve the right to change or modify specifications without prior notice. [www.satelco.ch](http://www.satelco.ch)

\* warranty ex works, normally 24 months, fixed at order. Information is current as of the date of publication. Subject to errors and modifications. / NOTE: Internal connections refer to connections inside the unit, generally mounted across a pin-header. External connections refer to those outside the box. Once mounted, only connections described as "front accessible" can be accessed by the customer.